Al Sharq Plas LLC

admin@alsharqplas.com www.alsharqplas.com

P.O.Box: 112004, Abu Dhabi, UAE Phone: +971 2 5501770 Fax : +971 2 5501171

Our Products

Heavy Duty Films

FFS Rolls

LDPE Bags and Sacks

Shrink Hood

Stretch Hood

Converting Films

Lamination Grade Films

Hi-Clarity Films For Printing

Shrink Films

Wrapping Films

Cast PE Stretch Film

Top and Bottom Sheet Film







Shrink film offers superb performance in holding and protecting products subject to frequent handling and transport. The film shrinks in both directions depending on the goods to be packed. It is also important to use the right structure of shrinkage. Shrink film is a well-established and cost effective method of collating cans, bottles, cartons and palletized goods, and also offers the transportation benefit of low weight. In addition, shrink film is suitable for recycling and incineration.



Al sharq Plas offers a wide range of products to cater for your needs and options including colour.

UV additives can be added to prevent the UV rays from damaging the item underneath the cover and also to prevent premature breakdown of the shrink film itself.



Some of the highlighting attributes of our shrink films include:

- 1. Excellent transparency
- 2. Good mechanical properties
- 3. Excellent printability
- 4. High shrinking capability at lower temperature.

Our shrink films provide dust free protection to all the packed products. Being manufactured on wide width robust state-of-the art film lines, and made from qualitative polyolefin films.

| SHRINK FILMS - PRODUCT INFORMATION | | |
|------------------------------------|--------|--------------|
| DESCRIPTION | UNIT | VALUE |
| THICKNESS | μm | 20 to 200 |
| ROLL LENGTH | mm | Customised |
| ROLL WIDTH | mm | upto 3200 mm |
| SHRINKAGE (MD) | % | 50 - 60 |
| SHRINKAGE (TD) | % | 10 - 20 |
| TENSILE STRENGTH @ BREAK (MD) | kg/cm2 | 300 |
| TENSILE STRENGTH @ BREAK (TD) | kg/cm2 | 270 |
| ELONGATION @ BREAK (MD) | % | 600 |
| ELONGATION @ BREAK (TD) | % | 800 |